



Override Protection Programs

'Down-Force Overload System' - Protects tool from excessive pressure and weight by shutting off.
 'Temperature Over-heat System' - Monitors temperature of internal electronic systems and will shut down tool until it is cool enough to prevent internal damage.

Specifications

Length: 7" Width: 2.5" Height: 4"
 12 Foot Long Cord / 1.4 Pounds

Portable

Sand on-site or in a production environment. Plugs directly into standard 110 volt outlet. Compact and lightweight.



Dust Free Sanding

Available in Central Vacuum which connects to a stand alone vacuum system.

More Power

350 watt brush-less outer-runner motor is constructed with bigger magnets providing greater torque which saves energy compared to inner-runner motors.



Speeds

3 operational speeds:
 4,000, 7,000 & 9,000 RPM.

Cutting-Edge Design

Low-profile design with ergonomic hand grip for enhanced control and comfort for both right & left-handed operators. Balanced wrist support for two-handed sanding.

Cooling Fan

Patented spindle bearing fan enhances life by keeping motor & bearings at a lower temperature

Longer Life

Computer board completely protected with patented rubberized seal preventing environmental contamination. No lubrication required and maintenance free.

Certified Tool Repair

Qualified service technicians & All OEM parts available.

3" X 4" Electric Sanders

ELECTRIC BRAW